

產品一覽表 Series Table

Series	Series Features	temp (°C)	voltage (VDC)	cap (μF)	load life	Page
貼片品 Surface Mount Type						
VSS	Surface Mount Type General Purpose (貼片標準品)	-40 ~ +85	4 ~ 100	0.1 ~ 1500	2000Hrs	18
VNS	Bi-polar Surface Mount Type (無極性貼片品)	-40 ~ +85	6.3 ~ 50	0.1 ~ 100	1000Hrs	21
VKS	Surface Mount Type General Purpose (貼片標準品)	-40 ~ +105	4 ~ 100	0.1 ~ 1500	1000Hrs	24
小型鋁電解電容 Miniature Aluminum Electrolytic Capacitors						
小型品 Miniature Type						
CD11W SSM	5mmL (高), +85°C	-40 ~ +85	4 ~ 50	0.1 ~ 470	1000Hrs	27
CD26K SKF	5mmL (高), +105°C	-40 ~ +105	4 ~ 50	0.1 ~ 470	1000Hrs	29
CD11C SSS	7 (9)mmL(高), High (高) C/V(化)	-40 ~ +85	6.3 ~ 50	0.1 ~ 470	1000Hrs	31
CD26C SKS	7mmL (高), -40°C ~ +105°C	-40 ~ +105	6.3 ~ 50	0.1 ~ 470	1000Hrs	33
標準品 General Purpose						
CD110X SGS	Standard (標準品)	-40 ~ +85	6.3 ~ 450	0.1-22000	2000Hrs	35
CD268 SKM	+105°C, Standard (標準品)	-40 ~ +105	6.3 ~ 450	0.1-33000	1000 ~ 2000Hrs	38
SKG	-55°C ~ +105°C, Standard (標準品)	-55 ~ +105	6.3 ~ 450	0.1-22000	1000 ~ 2000Hrs	41
低阻抗品 Low Impedance Type						
SZM	5mmL (高), +105°C, Low Impedance (低阻抗)	-40 ~ +105	6.3 ~ 35	1 ~ 470	1000Hrs	44
SZS	7mmL (高), +106°C, Low Impedance (低阻抗)	-40 ~ +105	6.3 ~ 35	4.7 ~ 470	1000Hrs	46
CD288H SGF	+105°C, High Ripple Current (高紋波) Low Impedance (低阻抗)	-40 ~ +105	6.3 ~ 450	1 ~ 18000	2000 ~ 4000Hrs	48
CD263L SRS	+105°C, High Ripple Current (高紋波) Low Impedance (極低阻抗)	-40 ~ +105	6.3 ~ 450	1 ~ 18000	3000 ~ 7000Hrs	53
長壽命品 High Reliability Type						
SRL	Long Life Assurance (長壽命) High Ripple Current (高紋波)	-40 ~ +105	6.3 ~ 450	1-22000	3000 ~ 8000Hrs	58
SRD	Long Life Assurance (長壽命) High Ripple Current (高紋波)	-25 ~ +105	160 ~ 450	10-330	8000-10000Hrs	63
無極性品 Non-polarized Type						
CD11N SNM	5mmL (高), Nonpolar (無極性)	-40 ~ +85	6.3 ~ 50	0.1 ~ 47	1000Hrs	65
CD71C SNS	7mmL (高), Nonpolar (無極性)	-40 ~ +85	6.3 ~ 50	0.1 ~ 220	1000Hrs	67
CD71 SNP	Nonpolar (無極性)	-40 ~ +85	6.3 ~ 100	0.47 ~ 6800	1000Hrs	69
CD71H SNH	+105°C, Nonpolar (無極性)	-40 ~ +105	6.3 ~ 100	0.47 ~ 1000	1000Hrs	71
低漏電品 Low Leakage Type						
SLF	5mmL(高), Low Leakage Current (低漏電)	-40 ~ +105	4 ~ 50	0.1 ~ 100	1000Hrs	73
SLZ	7mmL(高), Low Leakage Current (低漏電)	-40 ~ +105	6.3 ~ 50	0.1 ~ 220	1000Hrs	75
CD113H SLL	Low Leakage Current (低漏電)	-40 ~ +105	6.3 ~ 100	1 ~ 3300	1000Hrs	77
SLT	Time Circuit Use (計時回路用)	-40 ~ +85	10 ~ 50	1 ~ 470	2000Hrs	79
SLN	Low Noise Purpose (低噪音)	-40 ~ +85	6.3 ~ 100	0.47 ~ 47	1000Hrs	80

產品一覽表 Series Table

Series	Series	Features	temp (°C)	voltage (VDC)	cap (μF)	load life	Page
音響用品 For Audio Type							
	SFM	5mmL (高) , For Audio (音響)	-40 ~ +85	4 ~ 50	0.1 ~ 470	1000Hrs	81
	SFS	7mmL (高) , For Audio (音響)	-40 ~ +85	6.3 ~ 50	0.1 ~ 220	1000Hrs	83
CD72	SFA	Standard (標準品) , For Audio (音響)	-40 ~ +85	6.3 ~ 100	0.1 ~ 10000	1000Hrs	85
	SFN	Bi-polar (無極性) , For Audio (音響)	-40 ~ +85	50	1 ~ 68	-----	87
閃光燈用品 For Photo Flash Type							
CD17S	SPF	Photo Flash Use (閃光燈用品)	-25 ~ +55	330	36 ~ 300	5000times	88
CD17	SPS	Recharging And Discharging in Flash (閃光燈充電用)	-25 ~ +55	330,360	150 ~ 1500	5000times	89
大型鋁電解電容器 Large Can Aluminum Electrolytic Capacitors							
標準品 Standard Type							
CD293	SLP	Lug/Snap-in Terminal Type Standard (插入/自立型, 標準品)	-40 (25) ~ +85	10 ~ 450	56 ~ 82000	2000Hrs	92
	SAP	Lug/Snap-in Terminal Type for Audio (插入/自立型, 音響電容)	-40 ~ +85	16 ~ 100	680 ~ 10000	1000Hrs	98
CD293H	SHP	Lug/Snap-in Terminal Type, Wide Temperature (插入/自立型)	-40 (25) ~ +105	10 ~ 450	47 ~ 56000	2000Hrs	100
高可靠品 High Reliability Type							
CD294	SKP	Lug/Snap-in Terminal Type, Long Life (插入直立型, 長壽命)	-40 (25) ~ +105	10 ~ 450	47 ~ 56000	3000Hrs	106
CD296	SSP	Lug/Snap-in Terminal Type, Long Life (插入直立型, 長壽命)	-40 (25) ~ +105	160 ~ 450	56 ~ 1500	7000Hrs	112
特殊品 Special Type							
CD137	SWF	Screw Terminal Type, Long Life Assurance (螺釘型, 長壽命保證)	-40 (25) ~ +105	10 ~ 450	330 ~ 390000	5000Hrs	115